

FIBERGLASS TAPES



Our tapes are constructed of high quality type E glass that will not burn and will withstand continuous exposure to temperatures of 1000°F (540°C). This material resists most acids and alkalis; is unaffected by most bleaches and solvents; and is highly flexible and conformable.

Applications include boiler, coke oven, industrial oven, and wood stove doors; crucible packing and pollution control equipment; high temp tying and lacing cords; and pipe wrap.

Most tape products are available in black. In addition, any plain knit tape can be coated with high temperature flame resistant silicone rubber.

KNITTED FIBERGLASS TAPES

MATERIALS

Type E Fiberglass

AVAILABLE CONSTRUCTION OPTIONS

Knitted
Bolt-hole

MAXIMUM CONTINUOUS TEMPERATURE

1000°F (540°C)

SIZE RANGE

1/8" (3.2mm) X 1" (25.4mm) - 5" (127mm)

AVAILABLE OPTIONS

Special bulk packaging to maximize productivity and minimize waste
Coatings (vermiculite, silicone)
Colors (white, black)

TYPICAL INDUSTRIES

Boiler, OEM, Engine Exhaust, Industrial Ovens, Locomotive, Metals

DAVLYN FIBERGLASS TAPES			
Nominal Width		DAVLYN Part Number	
in.	mm	1/8" KNITTED	1/8" BOLT-HOLE
1	25.4	F-201601-00-00	F-211601-00-00
1-1/4	32	F-202001-00-00	F-212001-00-00
1-1/2	38	F-202401-00-00	F-212401-00-00
1-3/4	44	F-202801-00-00	F-212801-00-00
2	51	F-203201-00-00	F-213201-00-00
2-1/2	64	F-204001-00-00	F-214001-00-00
3	76	F-204801-00-00	F-214801-00-00
4	102	F-206401-00-00	F-216401-00-00
5	127	F-208001-00-00	F-218001-00-00

